

DCS200S - 1 - (24, 10) P/N 94043

Behlman's DCS200 series of COTS power supplies are low cost, highly reliable, switch mode units built for high-end industrial or MIL applications. The DCS200 can accept a wide range of inputs and can supply a variety of DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications and designed to meet the input power requirements of MIL-STD-704 and RTCA-DO160. Units are Base Plate cooled.

INPUT Input Transient protection: Per Mil-STD-704

-1: 85-265 VAC, 47-440 Hz, Power Factor Corrected

OUTPUT: **24VDC @ 10A**

Load Regulation: 0.2% Maximum (0-100%)
Line Regulation: 0.2% Maximum
PARD-Ripple & Noise: 150 mV (0-10Mhz)
Current Limit: Over current & Short Circuit protection.
Over voltage: 140% max.
Efficiency: 75% typical



GENERAL CHARACTERISTICS-see O&C drawing 24054

Isolation
Input to Output: 1000 VDC
Input to Case: 2500 VDC
Output to Case: 200 VDC
Dimensional Data: 8.75"L X 5.0"W X 1.18"H
Weight: 2.4 lbs
J1- Input: 5 pin connector
J2- Output: 30 pin connector

ENVIRONMENTAL: Designed to meet the following MIL Standards

Operating Temperature: -40 to +85 degrees C Base Plate
Storage Temperature: -55 to + 100 degrees C
Shock: MIL-S-901; MIL-STD-810
Vibration: MIL-STD-167; MIL-STD-810; RTCA/DO-160
Humidity: MIL-STD-810
EMI/EMC: MIL-STD-461C/D; RTCA/DO-160D. RE102 with proper shielding.

Proudly made

in the U.S.A.



www.behlman.com

ORBIT POWER GROUP
Behlman Electronics

Headquarters:
80 Cabot Court, Hauppauge, NY 11788
631 435-0410 800 874-6727
Fax: 631 951-4341

2363 Teller Road, Suite 108
Newbury Park, CA 91320
805 375-7046 800 456-2006
Fax: 805 498-2147

sales@behlman.com